

VERSAL INSERT

Linear Fire (conventional flue system)

DECORATION

Logs & chips

CONTROL OPTIONS



STANDARD



OPTIONAL



COMPATIBLE



Easy to install



Ambient LED illumination

VERSAL INSERT

	350 mm 13 3/4"	550 mm 21 5/8"	700 mm 27 9/16"	850 mm 33 7/16"
	(NG) max. 3.0 kW 10 236 BTU/h (LPG) max. 3.8 kW 12 966 BTU/h	(NG) max. 4.5 kW 15 355 BTU/h (LPG) max. 4.9 kW 16 719 BTU/h	(NG) max. 5.2 kW 17 743 BTU/h (LPG) max. 5.9 kW 20 132 BTU/h	(NG) max. 7.4 kW 25 250 BTU/h (LPG) max. 7.6 kW 25 932 BTU/h
	(NG) max. 0.32 m³/h 11.3 ft³/h (LPG) max. 0.30 kg/h 0.66 lbs/h	(NG) max. 0.48 m³/h 17.0 ft³/h (LPG) max. 0.39 kg/h 0.86 lbs/h	(NG) max. 0.55 m³/h 19.4 ft³/h (LPG) max. 0.47 kg/h 1.03 lbs/h	(NG) max. 0.79 m³/h 27.9 ft³/h (LPG) max. 0.60 kg/h 1.32 lbs/h
	Conventional			
	230 V / [US] 115 V			



VERSAL INSERT (350mm)



VERSAL INSERT (550mm)



VERSAL INSERT (700mm)



VERSAL INSERT (850mm)